

Technical Data Sheet

1-Ear Clamps, 2-Ear Clamps

Product Group 153/154, 101 & 151



Connecting Technology



Compact one-piece clamp: for robust, secure connections, miniature sizes

Clamp ear: fast and simple installation, visible deformation provides evidence of proper closure

Deburred edges: reduced risk of damage to parts being clamped

With insert

Pre-shaped insert: effective and powerful all-round seal

1-Ear Clamps Product Group 153/154

Material

153 Stainless Steel, Material no. 1.4301/UNS S30400

154 Clamp: Stainless Steel, Material no. 1.4301/UNS S30400

Insert: Stainless Steel, Material no. 1.4310/UNS S30100

Size range

153 3.3 – 30.7 mm

154 2.9 – 30.0 mm

Some sizes are only available if an appropriate minimum quantity is ordered.

Process

The manufacturing process for OETIKER 1-Ear and 2-Ear Clamps commences with the spiral roll-forming and welding of raw material into lengths of tube, a technique developed to obtain a robust, continuous welded ring.

OETIKER 1-Ear Clamps with insert

This type of clamp combines the geometry and properties of the 1-Ear Clamp with an insert made of stainless steel.

These clamps are ideal for demanding applications involving soft or hard rubbers and plastics. The thin-walled insert ring (up to 0.3 mm thick), with an oval protrusion that locates in the ear space, bridges the ear gap and ensures almost uniform compression around the whole circumference of a clamp.

Edge condition


Burrs generated during the shearing and forming processes are entirely eliminated in a barrel-finishing operation.

Closure

By using an OETIKER closing tool to pinch the clamp ear, the diameter of the clamp is reduced. This diameter reduction is proportional to the ear width.

The maximum reduction in diameter is given by the formula:

$$\text{Max. diameter reduction} = \frac{\text{Ear-width (s)}}{\pi}$$



2-Ear version: [extended clamping range](#)

Compact one-piece clamp: [for robust, secure connections](#)

Clamp ear: [fast and simple installation, visible deformation provides evidence of proper closure](#)

Deburred edges: [reduced risk of damage to parts being clamped](#)

2-Ear Clamps Product Group 101 & 151

Material

101 Steel, Material no. 1.0338/SAE 1008/1010, zinc-plated

151 Stainless Steel, Material no. 1.4301/UNS S30400

Size range

4.1 – 46.0 mm

[Some sizes are only available if an appropriate minimum quantity is ordered.](#)

OETIKER 2-Ear Clamps

The ears of these clamps do not have a dimple and nearly double the clamping range, compared to the 1-ear clamp. 2 ears provide a degree of elasticity to accommodate changes in size of the parts being joined, such as that which may be caused by thermal expansion or vibration.

Installation techniques are similar to those for 1-Ear Clamps, but the force applied when closing the second ear may react against the opposing closed ear and make a second crimping operation necessary. For perfect sealing, the ears must be adequately closed during installation.

Assembly recommendations

The ears of these clamps should be closed with the recommended, uniform force (known as force priority). This method will result in a constant, reproducible stress within the clamp material, without overloading either the clamp or the parts being assembled. The nominal diameter of the clamp should always be chosen so that, when installed with the correct clamping force, the ears are almost closed.

Complete process monitoring and 100% process documentation are available using the “Electronically Controlled Pneumatic Power Tool” OETIKER ELK 01.

Closing force

The following table shows the average applied closing force for different material dimensions.

Average applied closing force

Material dimensions	Closing force (N)		Manual pincer*	Recommended pneumatic pincer**
	Zinc-plated steel	Stainless		
Product Group 153				
03.3 – 11.0	–	1400	14100082, 14100083	HO 2000
11.3 – 20.7	–	2300	14100082, 14100083	HO 3000
21.0 – 30.7	–	2800	14100082, 14100083	HO 3000
Product Group 154				
03.3 – 11.8	–	1500	14100082, 14100083	HO 2000
12.0 – 20.7	–	2500	14100082, 14100083	HO 3000
21.0 – 30.7	–	3600	14100082, 14100083	HO 4000
Product Group 101 & 151				
0041 – 1720	2200	2500	14100082, 14100083	HO 3000
1922 – 4346	3400	3600	14100082, 14100083	HO 4000

* 14100082 Standard pincer

14100083 Standard pincer with side jaws

** With appropriate closing force setting

Important note

These figures are intended as a guide, they may vary depending on the type and tolerances of parts being clamped. To ensure optimum clamp selection, we recommend making functional tests with several assemblies.

Order information

Item No.	Ref. No.	Ear width inside (mm)	Size range (mm)	Item No.	Ref. No.	Ear width inside (mm)	Size range (mm)
1-Ear Clamps, stainless				1-Ear Clamps, stainless			
15300000	03.3R	1.4	2.9 – 3.3	15300021	13.3R	6.5	11.3 – 13.3
15300001	03.5R	1.4	3 – 3.5	15300022	13.8R	6.5	11.8 – 13.8
15300002	04.1R	2.5	3.3 – 4.1	15300023	14.0R	6.5	12 – 14
15300054	04.6R	3	3.8 – 4.6	15300024	14.5R	6.5	12.5 – 14.5
15300003	05.1R	3.2	4.1 – 5.1	15300025	15.0R	6.5	13 – 15
15300055	05.6R	3.2	4.6 – 5.6	15300026	15.5R	6.5	13.5 – 15.5
15300004	06.1R	3.2	5.1 – 6.1	15300027	16.0R	7	13.8 – 16
15300005	06.6R	3.2	5.6 – 6.6	15300028	16.5R	8	14 – 16.5
15300006	07.0R	3	6.1 – 7	15300029	16.8R	7	14.6 – 16.8
15300007	07.5R	3.5	6.5 – 7.5	15300030	17.5R	7	15.3 – 17.5
15300008	08.0R	4	6.8 – 8	15300031	18.5R	7	16.3 – 18.5
15300009	08.3R	4	7.1 – 8.3	15300032	19.5R	7.5	17.2 – 19.5
15300010	08.7R	4	7.5 – 8.7	15300033	20.0R	7.5	17.7 – 20
15300011	09.0R	5	7.5 – 9	15300034	20.7R	9	17.9 – 20.7
15300012	09.5R	5	8.1 – 9.5	15300035	21.0R	7.5	18.7 – 21
15300013	10.0R	5	8.5 – 10	15300036	21.8R	7.5	19.5 – 21.8
15300014	10.5R	5	9.1 – 10.5	15300037	22.5R	8.5	19.9 – 22.5
15300015	11.0R	5.5	9.3 – 11	15300038	23.5R	8.5	21 – 23.5
15300016	11.3R	5.5	9.6 – 11.3	15300040	24.5R	9	21.7 – 24.5
15300017	11.8R	5.5	10.1 – 11.8	15300041	25.5R	9	22.7 – 25.5
15300018	12.0R	6.5	10.1 – 12	15300043	26.3R	8.5	23.6 – 26.3
15300019	12.3R	6.5	10.3 – 12.3	15300044	27.0R	9.5	24.1 – 27
15300020	12.8R	6.5	10.8 – 12.8	15300045	30.7R	11	27.2 – 30.7

Order information

Item No.	Ref. No.	Ear width inside (mm)	Size range (mm)	Item No.	Ref. No.	Size range (mm)
1-Ear Clamps with insert, stainless				2-Ear Clamps, zinc-plated		
15400010	03.3RER	1.4	2.5 – 2.9	10100000	0041	3.1 – 4.1
15400011	03.5RER	1.4	2.7 – 3.1	10100001	0045	3.5 – 4.5
15400012	04.1RER	2.5	2.9 – 3.7	10100002	0305	3.4 – 5
15400063	04.6RER	3	3.4 – 4.2	10100004	0507	5 – 7
15400013	05.1RER	3.2	3.7 – 4.7	10100008	0709	7 – 9
15400064	05.6RER	3.2	4.2 – 5.2	10100011	0811	8.1 – 11
15400014	06.1RER	3.2	4.7 – 5.7	10100016	1113	10.8 – 13
15400015	06.6RER	3.2	5.2 – 6.2	10100019	1315	12.5 – 15
15400016	07.0RER	3	5.6 – 6.5	10100022	1517	14 – 17
15400017	07.5RER	3.5	5.9 – 7	10100097	1619	16 – 19
15400018	08.0RER	4	6.3 – 7.5	10100027	1720	16.2 – 20
15400019	08.3RER	4	6.6 – 7.8	10100029	1922	18 – 22
15400020	08.7RER	4	7 – 8.2	10100030	2023	19 – 23
15400021	09.0RER	5	7 – 8.5	10100032	2225	21 – 25
15400022	09.5RER	5	7.5 – 9	10100034	2327	22.5 – 27
15400023	10.0RER	5	8 – 9.5	10100035	2528	24 – 28
15400024	10.5RER	5	8.5 – 10	10100037	2731	26.3 – 31
15400025	11.0RER	5.5	8.8 – 10.5	10100041	3134	29.3 – 34
15400026	11.3RER	5.5	9.1 – 10.8	10100043	3437	32 – 37
15400027	11.8RER	5.5	9.6 – 11.3	10100045	3740	35 – 40
15400028	12.0RER	6.5	9.5 – 11.5	10100047	4043	37.6 – 43
15400029	12.3RER	6.5	9.8 – 11.8	10100049	4346	40.6 – 46
15400030	12.8RER	6.5	10.3 – 12.3	2-Ear Clamps, stainless		
15400031	13.3RER	6.5	10.6 – 12.6	15100000	0041R	3.1 – 4.1
15400032	13.8RER	6.5	11.1 – 13.1	15100001	0045R	3.5 – 4.5
15400033	14.0RER	6.5	11.3 – 13.3	15100002	0305R	3.4 – 5
15400034	14.5RER	6.5	11.8 – 13.8	15100003	0507R	5 – 7
15400035	15.0RER	6.5	12.3 – 14.3	15100004	0709R	7 – 9
15400036	15.5RER	6.5	12.8 – 14.8	15100023	0811R	8 – 11
15400037	16.0RER	7	13.1 – 15.3	15100006	1113R	11 – 13
15400038	16.5RER	8	13.2 – 15.8	15100007	1315R	12.5 – 15
15400039	16.8RER	7	13.9 – 16.1	15100008	1517R	14 – 17
15400040	17.5RER	7	14.6 – 16.8	15100010	1720R	16.2 – 20
15400041	18.5RER	7	15.6 – 17.8	15100011	1922R	18.1 – 22
15400042	19.5RER	7.5	16.5 – 18.8	15100012	2023R	19.1 – 23
15400043	20.0RER	7.5	17.1 – 19.3	15100013	2225R	21.1 – 25
15400044	20.7RER	9	17.1 – 20	15100014	2327R	22.5 – 27
15400045	21.0RER	7.5	18 – 20.3	15100015	2528R	24 – 28
15400046	21.8RER	7.5	18.8 – 21.1	15100016	2731R	26.3 – 31
15400065	22.5RER	8.5	19.2 – 21.8	15100018	3134R	29.3 – 34
15400048	23.5RER	8.5	20.2 – 22.8	15100019	3437R	32 – 37
15400049	24.5RER	9	21 – 23.8	15100020	3740R	35 – 40
15400050	25.5RER	9	22 – 24.8	15100021	4043R	37.6 – 43
15400051	26.3RER	8.5	23 – 25.6	15100022	4346R	40.6 – 46
15400052	27.0RER	9.5	23.3 – 26.3			
15400053	30.7RER	11	26.5 – 30			

The OETIKER Group: www.oetiker.com

Headquarters Switzerland
Hans Oetiker AG
Maschinen- und Apparatefabrik
Oberdorfstrasse 21
CH-8812 Horgen (Zürich)
T +41 44 728 55 55
F +41 44 728 55 15
info@ch.oetiker.com

Austria
Hans Oetiker
Maschinen- und Apparatebau
Ges.m.b.H.
Eduard-Klinger-Strasse 19
A-3423 St. Andrä-Wördern
T +43 2242 33 994-0
F +43 2242 33 997
info@at.oetiker.com

Belgium
Oetiker Belgium N.V./S.A.
Maaltecenter – Blok "G"
Derbystraat 301
9051 Gent/St. Denijs-Westrem
T +32 9 252 25 55
F +32 9 252 25 56
info@be.oetiker.com

Canada
Oetiker Limited
203 Dufferin Street South
P. O. Box 5500
Alliston, Ontario L9R 1W7
T +1 705 435 4394
info@ca.oetiker.com

P. R. China
Oetiker Industries (Tianjin) Ltd.
10 Shuangchenzhong Road
Beichen High Tech Industrial Park
Tianjin 300400
T +86 22 2697 1183
F +86 22 2697 1380
info@cn.oetiker.com

Czech Republic
Hans Oetiker spol. s r. o.
Videnska 116
CZ-37833 Nová Bystrice
T +420 384 386513
F +420 384 386386
info@cz.oetiker.com

France
Oetiker Sarl
9, rue Jean Moulin
ZA du Pré Fusé
F-77348 Pontault-Combault Cedex
T +33 1 60 29 90 39
F +33 1 64 40 90 23
info@fr.oetiker.com

Germany
Hans Oetiker
Metallwaren- & Apparatefabrik GmbH
Üsenbergerstrasse 13
D-79346 Endingen a. K.
T +49 76 42 6 84-0
F +49 76 42 6 84-125
info@de.oetiker.com

Kurt Allert GmbH & Co. KG
Postfach 1160
Austrasse 36
D-78727 Oberndorf a. N.
T +49 74 23 87 70-0
F +49 7 4 23 87 70-87
info@allert.oetiker.com

Hong Kong
Oetiker Far East Limited
2210 Tuen Mun Central Square
22 Hoi Wing Road
Tuen Mun NT
T +852 2459 8211
F +852 2459 8322
info@hk.oetiker.com

Hungary
Oetiker Hungaria KFT
Vasvári P. U. 11
H-9800 Vasvár
T +36 94 370 630
F +36 94 370 533
info@hu.oetiker.com

India
Oetiker India Private Ltd.
N-14, Additional Patalganga
Industrial Area
Village Chavane, Khalapur
Rasayani 410 220
Dist. Raigad
T +91 2192 250107-12
F +91 2192 250105
info@in.oetiker.com

Japan
Oetiker Japan Co. Ltd.
Kaneko Bldg. A
5-3-5 Nakamachi-dai, Tsuzuki-ku
Yokohama 224-0041
T +81 45 949 3151
F +81 45 949 3152
info@jp.oetiker.com

Netherlands
Oetiker Benelux B.V.
Hertzstraat 38
NL-6716 BT Ede
T +31 318 63 71 71
F +31 318 63 34 89
info@nl.oetiker.com

Spain
Oetiker España, S. A.
Pol. Ind. Las Salinas
C/Puente, 18
E-11500 El Puerto
de Santa María (Cádiz)
T +34 956 86 04 40
F +34 956 87 17 07
info@es.oetiker.com

United Kingdom
Oetiker UK Limited
Foundry Close
GB-Horsham, Sussex RH13 5PX
T +44 1403 26 04 78
F +44 1403 24 06 90
info@uk.oetiker.com

USA
Oetiker, Inc.
6317 Euclid Street
Marlette, Michigan 48453-0217
T +1 989 635 3621
F +1 989 635 2157
info@us.oetiker.com